



ULTRA Ultrasonic Immersion Washer



Oil Sparger & Weir Tank



In stainless steel

The ULTRA Ultrasonic Series features a robust stainless steel design for heavy duty parts washing applications.

During the wash cycle, the pneumatically operated lift platform lowers the workload into the tank and agitates with an up-and-down motion, while the powerful ultrasonic energy quickly removes soils form hard to clean areas.





ULTRA Ultrasonic Immersion Washer

SPECIFICATIONS		U700	U900	U1100	U1300
Platform	Inches	27.6"x15.7"	35.4"x15.7"	43.3"x19.7"	51.2"x23.6"
Load Height	Inches	11.8"	15.7"	15.7"	15.7"
Operating Temperature	°F	170	170	170	170
Weight Capacity	Lbs	180	550	550	770
Tank Capacity	Gal	70	100	140	180
Tank Heater	kW	6	8	10	12
Ultrasonic Power	W	1500	2000	3000	4000
Ultrasonic Frequency	kHz	25	25	25	25
Amperage	Α	17	23	30	38
Thermal Insulation	-	Standard	Standard	Standard	Standard
Voltage	V	460	460	460	460
Phase	Ph	3	3	3	3
Overall Dimensions	LxWxH Inches	60"x38"x59"	68"x38"x67"	76"x42"x67"	84"x46"x70"

We reserve the right to modify without notice.

STANDARD FEATURES

- Stainless Steel Construction
- Automatic Immersion Lift Platform
- PLC Control
- Compressed Air Blow-Off Gun
- Oil Sparger & Weir Tank

- Low Water Shutoff
- Thermostat Controlled Solution Heater
- Adjustable Leveling Feet
- Thermally Insulated